







LUXEON 3014 with FreshFocus Technology™

Accentuating freshness and overall visual appeal, making food irresistible



The LUXEON 3014 with FreshFocus Technology creates the most impactful lighting ever available by accentuating the freshness and overall visual appeal of a variety of fresh food areas such as supermarkets, delis, butcher shops and bakeries. LUXEON 3014 with FreshFocus Technology is an industry standard compatible 3.0mm x 1.4mm x 0.75mm footprint with specialty color and spectrum targeted for highlighting the colors of different foods.

FEATURES AND BENEFITS

Industry standard footprint and package compatible with existing designs

1/9th ANSI micro-color binning enabling tight color control

Rectangular package design allows for increased uniformity

Drive at maximum current (120mA) for superior value

PRIMARY APPLICATIONS


Specialty Lighting


- Fresh Foods
- Linear Display

LUXEON 3014 with FreshFocus Technology product performance at 60mA, T_i=25°C.

| PRODUCT SPECTRUM | MINIMUM CRI [1] | LUMINOUS FLUX ^[1] (lm) | | TYPICAL LUMINOUS | PART NUMBER |
|---------------------|--------------------|-----------------------------------|---------|---------------------|--------------------|
| | | MINIMUM | TYPICAL | EFFICACY (lm/W) | ., |
| Marbled Meat | 80 | 14.5 | 17.0 | 86.0 | L130-MMSA001400001 |

Mechanical Dimensions.





Notes:

- Drawings are not to scale.
- Drawings are not to scale.
 All dimensions are in millimeters.

©2018 Lumileds Holding B.V. All rights reserved. LUXEON is a registered trademark of the Lumileds Holding B.V. in the United States and other countries.

lumileds.com

Neither Lumileds Holding B.V. nor its affiliates shall be liable for any kind of loss of data or any other damages, direct, indirect or consequential, resulting from the use of the provided information and data. Although Lumileds Holding B.V. and/or its affiliates have attempted to provide the most accurate information and data, the materials and services information and data are provided "as is," and neither Lumileds Holding B.V. nor its affiliates warrants or guarantees the contents and correctness of the provided information and data. Lumileds Holding B.V. and its affiliates reserve the right to make changes without notice. You as user agree to this disclaimer and user agreement with the download or use of the provided materials, information and data. A listing of Lumileds product/patent coverage may be accessed at lumileds.com/patents.

Notes: 1. Lumileds maintains a tolerance of ± 2 on CRI and $\pm 7.5\%$ on luminous flux measurements.